

STAXX
STAXX MATERIAL HANDLING EQUIPMENT CO., LTD

ELECTRIC STACKER

WS10S-ei

Make
Your Job
Easier

www.staxxmhe.com



INTELLIGENT HANDLE

- ◆ VEHICLE WORKING STATUS DISPLAYING
- ◆ QUICK ERROR DETECTING
- ◆ ALL MAINTENANCE INFORMATION VISUALIZED



WS10/15S-ei

ELECTRIC STACKER

MODEL		WS10S-ei							WS15S-ei								
CHARACTERISTICS																	
1.1	Drive unit	Electric							Electric								
1.2	Operator type	Walkie							Walkie								
1.3	Capacity	Q	kg	1000							1500						
1.4	Load center distance	C	mm	600							600						
1.5	Wheel base	Y	mm	1275							1275						
WEIGHT																	
2.1	Service weight(with battery)		kg	335	390	415	440	455	465	376	420	452	485	504	517		
2.2	Service weight(without battery)		kg	295	350	375	400	415	425	336	380	413	445	464	477		
WHEEL																	
3.1	Tyre type driving wheels/loading wheels	PU							PU								
3.2	Size of loading wheels	Φd	mm	φ78							φ78						
3.3	Size of driving wheel	ΦD	mm	φ210							φ210						
3.4	Size of balance wheel		mm	φ124							φ124						
3.5	Wheel quantity		pcs	4							4						
SPECIFICATIONS																	
4.1	Lift height	h	mm	1600	2000	2500	3000	3300	3500	1600	2000	2500	3000	3300	3500		
4.2	Mast lower height	H	mm	2010	1535	1785	2035	2185	2260	2010	1535	1785	2035	2185	2260		
4.3	Mast extend height	H1	mm	2010	2490	2990	3490	3790	3990	2010	2490	2990	3490	3790	3990		
4.4	Overall length	L	mm	1750							1750						
4.5	Overall width	W	mm	820							820						
4.6	Fork dimensions		mm	54x160x1125							54x160x1125						
4.7	Width across forks	W1	mm	560/680							560/680						
4.8	Lowered height of fork	h1	mm	90							90						
4.9	Clearance	h2	mm	30							30						
4.1	Aisle width for pallets (1000 x 1200mm)		mm	2305							2305						
4.11	Aisle width for pallets (800 x 1200mm)		mm	2230							2230						
4.12	Min turning radius	Wα	mm	1470							1470						
PERFORMANCE																	
5.1	Travelling speed, laden/unladen		km/h	4.6/4.7							4.6/4.7						
5.2	Lifting speed, laden/unladen		mm/s	97/131	115/160	115/160	115/160	115/160	115/160	65/90	75/110	75/110	75/110	75/110	75/110		
5.3	Lowering speed, laden/unladen		mm/s	147/53	170/130	170/130	170/130	170/130	170/130	95/40	145/100	145/100	145/100	145/100	145/100		
5.4	Max. gradeability,laden/unladen		%	5/7							5/7						
5.5	Service brake type			Electronic							Electronic						
ELECTRIC ENGINE																	
6.1	Driving motor		kw	0.75							0.75						
6.2	Lifting motor		kw	2.2							2.2						
6.3	Battery voltage/capacity		V/Ah	12/75Ah x 2							12/75Ah x 2						
6.4	Battee size		mm	(260×172×170)×2							(260×172×170)×2						
6.5	Controller			STAXXA6101							STAXXA6101						

